



## FEATURES

- Available in 17" (432mm), 24" (610mm) and 36" (915mm) formats
- Standard processing speeds up to 100 feet (30 metres)/minute
- Handles cut sheet flexible or rigid coated media up to 0.5 inches (13mm) on bottom roller, or up to 14pt on top roller
- Patented, engraved roller system creates Smooth, Artisan, Fine Canvas, Crystal, Leather or Linen textures\*
- Optional proofing roller to watermark proofs
- Variable coating thickness from 8 to 14 microns
- Sensor activated light shields
- Multi-tank coating carousel
- Enclosed conveyor for dry, dust-free prints
- Automated start-up and shut-down
- Filtered recirculation system to maximize coating mileage
- Optional feeder and jogger available
- Optional ink preconditioning station available
- 1 year warranty parts/6 months labor

# DRYTAC®

**EXPERTS IN FINISHING SOLUTIONS**

## UV Curable Coater Delivers Different Textures and Sheen for Photo Projects

The VersaCoater™ PhotoMate is designed to coat photo projects like portraits, wedding photos, personalized photo albums and other custom photo projects. Capable of processing speeds up to 100 ft. (30m) / minute, the VersaCoater™ PhotoMate's dual path engineering can create your choice of Smooth, Artisan, Fine Canvas, Crystal, Leather or Linen textured finishes on the same machine\*. An optional custom proofing roller can also watermark proofs with your shop's logo or other custom watermark.

### Advanced engineering for a wide range of photo/print applications

PhotoMate delivers custom textured as well as smooth UV curable coatings on a variety of media types with equal ease. A multi tank carousel allows you to switch between different coating and cleaning combinations, allowing you to keep different coatings loaded in the machine for quick job set up.

### Built-in versatility

Compatible with photo, inkjet and digital presses such as iGen/Indigo/DocuColor/NexPress, the PhotoMate protects and adds value to your clients' photo albums and images. Used with the InstaCure Photo coatings that are ideal for silver halide or digital press prints, you can emboss, imprint or sign school pictures, wedding portraits, black and white prints and book covers after the prints have been coated. With the the optional Polymerized Ink Treatment System, you can coat onto hard to stick to media and highly infused wax based toner/ink systems, such as the Konica Minolta C6500. Rigid or flexible coated photo paper or other digital media up to 1/2-inch (13mm) thick can be coated with the PhotoMate without changeovers or modifications

### Low cost of ownership

A compact footprint and easy-to-operate features reduce space and staff training costs, making the VersCoater™ PhotoMate a lower cost to own machine than competitors' models. Automated start up and shutdown, semi-automatic cleaning and automatic drain, UV lamp ready monitor and a filtered coating re-circulating system all make operating the PhotoMate and managing project production easier.

\* The Smooth roller and one textured roller (Crystal unless otherwise specified) comes standard with the VersaCoater™ PhotoMate. Additional textured rollers can be ordered separately.

## TECHNICAL SPECIFICATIONS—VERSACOATER™ PHOTOMATE

### Coating Specifications:

Coating Thickness:	Variable 8 - 14 microns on all models		
Coating Technology:	100% UV curable - reverse roll / flood		
Process Speed:	30 - 100 ft (10 - 30 meters) / minute		
Coating Roller:	Proprietary		
Available Roller Textures:	Smooth and one textured roller come standard (ships with a Crystal textured roller unless otherwise specified). Optional: Artisan, Fine Canvas, Crystal, Leather, Linen and custom watermark proofing roller		
Sheet Thickness (min-max)	65 lb cover stock to 140lb cover stock		

### Dimensions:

	17" (43cm)	24" (61cm)	36" (91cm)
Max. Coat Width:	17" (43cm)	24" (61cm)	36" (91cm)
Coater Size: (L x W x H):	52" x 31" x 46" (132cm x 78cm x 116cm)	52" x 39" x 46" (132cm x 99cm x 116cm)	98" x 52" x 46" (249cm x 132cm x 116cm)
Crated Size (L x W x H):	67" x 40" x 52" (170cm x 101cm x 132cm)	67" x 49" x 52" (132cm x 124cm x 116cm)	74" x 64" x 52" (188cm x 162cm x 132cm)
Coater Net Weight:	609 lbs (276 kg)	920 lbs (417 kg)	1400 lbs (635 kg)
Crated Weight:	841 lbs (381.5 kg)	1160 lbs (526 kg)	1750 lbs (794 kg)

### Electrical Specifications:

Amperage:	25 Amps	30 Amps	50 Amps
Line Voltage:	208-240VAC 50/60Hz 1 ph (does not include cord)		

### Safety and Warranty

Safety Certification:	CE Standards
Emergency Shut Off:	Yes
Ventilation:	External ventilation or air purification highly recommended
Warranty:	1 year parts/6 months labor

### Order Codes

Coater & Curing Unit	VCPHM-17R2 (17")	VCPHM-24R2 (24")	VCPHM-36R2 (36")
Artisan Texture Roller	VC-PHM-ART-17 (17")	VC-PHM-ART-24 (24")	VC-PHM-ART-36 (36")
Fine Canvas Texture Roller	VC-FCTR17 (17")	VC-FCTR24 (24")	VC-FCTR36 (36")
Crystal Texture Roller	VC-CTR17 (17")	VC-CTR24 (24")	VC-CTR36 (36")
Linen Texture Roll	VC-LNTR17 (17")	VC-LNTR24 (24")	VC-LNTR36 (36")
Leather Texture Roll	VC-LTR17 (17")	VC-LTR24 (24")	VC-LTR36 (36")
Optional pre-treatment station for wax infused toners	VCPHM-IRK17 (17")	VCPHM-IRK24 (24")	VCPHM-IRK36 (36")

## COMPATIBLE INSTACURE UV CURABLE COATINGS

ICUVCDG	Digital Gloss
ICUVCDM	Digital Matte
ICUVCPG	Photo Gloss
ICUVVCP	Photo Lustre
ICUVVCPM	Photo Matte



**US TOLL FREE 1-800-280-6013**  
**CANADA TOLL FREE 1-800-353-2883**

**ON THE WEB:**  
[www.drytac.com](http://www.drytac.com)